



FILM BLOWING MACHINE PRODUCT CATALOG 2026 - 2027

Since 2008

YEAR FOUNDED

120+

COUNTRIES & REGIONS

123+

PATENTS GRANTED

1 to 9

BLOWN FILM LAYERS

www.layerquestar.com

FILM BLOWING MACHINE

LQ-700-2100

HDPE / LDPE FILM BLOWING MACHINE



MODEL	LQ-50-700	LQ-55-900	LQ-60-1100	LQ-65-1300	LQ-75-1600	LQ-85-2100
Suitable Materials	HDPE,LDPE,LLDPE	HDPE,LDPE,LLDPE	HDPE,LDPE,LLDPE	HDPE,LDPE,LLDPE	HDPE,LDPE,LLDPE	HDPE,LDPE,LLDPE
Film Width	100-600 mm	400-800 mm	500-1000 mm	800-1200 mm	1000-1500 mm	1500-1900 mm
Film Thickness	0.006-0.10mm	0.006-0.10mm	0.006-0.10mm	0.006-0.10mm	0.006-0.10mm	0.006-0.10mm
HDPE Max Output	60KG	80KG	100KG	100KG	120KG	150KG
LDPE Max Output	80KG	100KG	120KG	150KG	180KG	200KG
Screw Diameter	50mm	55mm	60mm	65mm	75mm	85mm
Screw L/D	30:1/32:1	30:1/32:1	30:1/32:1	30:1/32:1	30:1/32:1	30:1/32:1
Gerew L/D	146	173	180	200	200	225
Mear Motor	15KW	18.5KW	22KW	30KW	45KW	55KW
Air Blower	4KW	4KW	5.5KW	5.5KW	7.5KW	11KW
Total Power	25KW	30KW	45KW	55KW	80KW	100KW
HDPE Die Head	60mm	80mm	100mm	120mm	180mm	220mm
LDPE Die Head	120mm	150mm	220mm	250mm	350mm	450mm
Roller Width	700mm	900mm	1100mm	1300mm	1600mm	2100mm
Dimension/Weight	6×3×5.2m/3.5T	6×3×5.2m/4T	6×3.5×6.2m/4.5T	6×3.5×6.8m/5.5T	6×4×7.2m/6.5T	7×4.5×9.5m/8.5T

FILM BLOWING MACHINE

LQ-AB-1300-2200

AB TWO-LAYER AGRICULTURAL MULCHING
FILM BLOWING MACHINE



MODEL	LQ-AB-1300	LQ-AB-1700	LQ-AB-2200
Suitable Materials	LDPE,LLDPE,PBAT+PLA	LDPE,LLDPE,PBAT+PLA	LDPE,LLDPE,PBAT+PLA
Film Width	800-1200mm	1000-1600mm	1200-2000mm
Film Thickness	0.006-0.03mm	0.006-0.03mm	0.006-0.03mm
LDPE Max Output	150KG	160KG	220KG
PBAT Max Output	180KG	200KG	260KG
Screw Diameter	60mm×2	65mm×2	70mm×2
Screw L/D	30:1/32:1	30:1/32:1	30:1/32:1
Gear Box	180×2	200×2	200×2
Main Motor	22KW×2	30KW×2	37KW×2
Air Blower	7.5KW	7.5KW	11KW
Total Power	80KW	110KW	135KW
Die Head	250mm	350mm	450mm
Roller Width	1300mm	1700mm	2200mm
Dimension/Weight	6×4.5×6.8m/5.5T	6×5.5×7.2m/6.5T	7×6.5×9.5m/8T

FILM BLOWING MACHINE

LQ-ABA-700-1600

ABA LDPE/HDPE HIGH SPEED FILM BLOWING MACHINE
(WITH AUTOMATIC PLC WINDER)



MODEL	LQ-ABA-700	LQ-ABA-900	LQ-ABA-1100	LQ-ABA-1300	LQ-ABA-1600
Suitable Materials	HDPE,LDPE,LLDPE	HDPE,LDPE,LLDPE	HOPE,LDPE,LLDPE	HOPE,LDPE,LLDPE	HOPE,LDPE,LLDPE
Film Width	100-600mm	400-800mm	500-1000mm	600-1200mm	1000-1500mm
Film Thickness	0.006-0.10mm	0.006-0.10mm	0.006-0.10mm	0.006-0.10mm	0.006-0.10mm
HDPE Max Output	70KG	85KG	100KG	120KG	150KG
LDPE Max Output	85KG	110KG	120KG	150KG	180KG
Screw Diameter	45mm×2	50mm×2	50mm×2/55mm×2	55mm×2/60mm×2	60mm×2/65mm×2
Screw L/D	30:1/32:1	30:1/32:1	30:1/32:1	30:1/32:1	30:1/32:1
Gear Box	146×2	146×2	173×2	180×2	200×2
Main Motor	15KW×2	15KW×2	18.5KW×2	22KW×2	30KW×2
Air Blower	4KW	5.5KW×	5.5KW	7.5KW	7.5KW
Total Power	50KW	55KW	70KW	80KW	110KW
HDPE Die Head	60mm	80mm	100mm	120mm	150mm
LDPE Die Head	120mm	150mm	220mm	250mm	350mm
Roller Width	700mm	900mm	1100mm	1300mm	1600mm
Dimension/Weight	5×3.5×5.2m/4T	5×4×5.2m/4.5T	6×5.5×7.2m/6T	6.5×5.5×7.2m/7T	7×6×8.5m/8T

FILM BLOWING MACHINE

LQ-ABC-900-2200

ABC THREE-LAYER CO-EXTRUSION FILM BLOWING MACHINE



MODEL	LQ-ABC-900	LQ-ABC-1100	LQ-ABC-1300	LQ-ABC-1600	LQ-ABC-2200
Suitable Materials	LDPE,LLDPE,PBAT+PLA	LDPE,LLDPE,PBAT+PLA	LDPE,LLDPE,PBAT+PLA	LDPE,LLDPE,PBAT+PLA	LDPE,LLDPE,PBAT+PLA
Film Width	400-800mm	600-1000mm	800-1200mm	1000-1500mm	1500-2000mm
Film Thickness	0.02-0.15mm	0.02-0.15mm	0.02-0.15mm	0.02-0.15mm	0.02-0.15mm
Max Extrusion Output	150KG/H	170KG/H	180KG/H	220KG/H	280KG/H
Screw Diameter	45mm/50mm/45mm	50mm/55mm/50mm	55mm/60mm/55mm	60mm/65mm/60mm	65mm/75mm/65mm
Screw L/D	30:1/32:1	30:1/32:1	30:1/32:1	30:1/32:1	30:1/32:1
Gear Box	146×2/173×1	173×2/180×1	180×3	180×2/200×1	200×2/225×1
Main Motor	15.5/22/15.5KW	22/30/22KW	22/30/22KW	30/37/30KW	37/45/37KW
Air Blower	5.5KW×1/4KW×2	7.5KW×1/5.5KW×2	7.5KW	7.5KW	11KW
Total Power	100KW	130KW	130KW	185KW	230KW
Die Head	250mm	300mm	280mm	350mm	500mm
Roller Width	900mm	1100mm	1300mm	1600mm	2200mm
Dimension/Weight	6.5×5×6.2m/5.5T	7×5×6.8m/6.5T	8×5.5×6.8m/7.5T	8.5×6×7.8m/8.5T	9×7.5×9.5m/10T

FILM BLOWING MACHINE

LQ-5S-2300

FIVE-LAYER CO-EXTRUSION FILM BLOWING MACHINE
(WITH IBC SYSTEM)



MODEL	LQ-SS-2300 (WITH IBC)
Suitable Materials	LDPE, LLDPE, MLLDPE, MDPE
Film Width	2100mm
Film Thickness	0.03-0.15mm
Max Extrusion Output	400KG/H
Screw Diameter	60mm×5
Screw L/D	32:1
Gear Box	250×5
Main Motor	55KW×5 SERVO MOTOR
Air Blower	22KW×1 / 11KW×2
Total Power	500KW
Die Head	500mm
Roller Width	2300mm
Dimension/Weight	20×8.5×14.5m/25T



**ONE SUPPLIER.
ONE LINE.
ONE RESPONSIBILITY.**

✉ info@layerquestar.com

🌐 www.layerquestar.com

☎ +86 137 5083 0177